



Model FD6-130

Features

- High RPM application is available, specify this requirement when placing order.
- Left side mounted fitting holes and flow control valve are available.
- Capable of $\pm .0005$ with short dwell.



Spindle Options

(See page 51 for drawings and dimensions)

ER20	Pg. 51
JT6	Pg. 51
AS22	Pg. 51
MT3	Pg. 51
ER25	Pg. 51
JT6 Multi	Pg. 51
MT2	Pg. 51

Specifications (Unit: metric)

Hydraulic Pressure	280 ~ 350 P.S.I.
Drilling Capacity	5/8" (steel)
Stroke	4.7"
Max. Revolution/Minute	2,000RPM
Flow Control Valve	FCC-G02-4
Weight	70.5 lb
Cylinder Diameter	3"
Cylinder Area	Forward 6.70 IN ² , Backward 4.75 IN ²
Thrust Force	1900 lb @ 280 P.S.I.

Consumption Parts

O-Ring for Front Cover	P-58x2, G-75x1
O-Ring for Piston	P-70x2, G-45x1
O-Ring for Rear Cover	P-30x2, G-40x1, G-75x1
Spindle Bearing	a. 32005x1, 6005Zx1, 32004x1, 6004Zx1 b. 7005x2, 7004x2
Pulley Bearing	a. 6008Zx1, 51208x1 or 51108x1 b. 7008x2